



20" Heated Roll Ironer UD20F098

When only the highest quality finish will do, UniMac's heated roll flatwork finishers deliver seriously superior results. We offer seven models to meet the needs of any size operation.

Lower Utility Costs

The quality construction of UniMac ironers does more than ensure durability and lasting performance - it will also help you save on energy costs. Thicker steel and a 300° angle of contact allow our machines to achieve a lower Btu consumption, while our specialized micro control allows for a wide array of energy-saving settings.

Focused on Safety

Designed to be as safe as possible, a stop bar prevents operators from placing their hands too close to the machine, and a sophisticated alarm system indicates when any of the components are not working properly.

Peace of Mind

Our limited parts warranty includes non-textile components against failure from defect in material or workmanship during the first year.

Specifications

Roll Diameter - in (mm)	20" (500)	
Finishing Width - in (mm)	98" (2500)	
Ironing Speed - ft/m (m/m)	3-30 (1-9)	
Width - in (mm)	140 3/4" (3574)	
Depth - in (mm)	42 1/4" (1072)	
Height - in (mm)	46 1/8" (1171)	
Roll Motor - HP (kW)	.5 (.37)	
Roll Exhaust Motor - HP (kW)	2 x .34 (2 x .25)	
Roll Exhaust Duct - in (mm)	2 x 6" (2 x 150)	
Gas Heating		
Maximum Gas Input - Btu (kW)	187,623 (55)	
Gas Inlet - in (mm)	1" (22)	
Electrical Requirements - Circuit Breaker	120/60/1 * 15	
	230/50/3 * 6	
	400/50/3 * 6	
Electric Heating		
Capacity Resistances - HP (kw)	54 (40.5)	
Electrical Requirements - Circuit Breaker	208-240/60/3 * 125	
	230/50/3 * 125	
	400/50/3 * 63	
Steam Heating		
Steam Inlet - in (mm)	3/4" (19.5)	
Condensate Return - in (mm)	1/2" (12.7)	
Hourly Consumption - lb/hr (kg/hr)	147 (67)	
Min.-Max. Steam Pressure - psi (bar)	145 (10)	400/50/3 * 4
Shipping Weight - lb (kg)	2796 (1269)	
Approvals	CSA, ETL, CE	



Control Option