



## Softmount UX18PV

Capacity: 18 lb  
Control: P

### Flexible Installation

UniMac UX model softmount washer-extractors are the perfect choice for second-floor laundries or other installations where a poured foundation isn't an option. Plus, our efficient design uses 34% less space than some competitors' models, giving you more room to manage your laundry.

### Lower Utility Costs

Our softmount washer-extractors not only save on installation costs, but on utility costs as well. Our state-of-the-art Intelligent Drive system is designed to provide unique extraction speeds calibrated for different types of loads, so you'll never waste water or gas. Plus, the high-speed extraction will reduce your drying and finishing times, saving up to 40% on your gas and water bills when compared to a standard 85 G-Force washer.

### Worry-Free Performance

Featuring solid steel construction and heavy-duty precision bearings, our line of UX model washer-extractors consistently achieve high levels of efficiency, quality and durability.

### Versatility

With 39 customizable preset wash programs, you have the flexibility to tailor wash cycles to specific pieces. Linens that receive the best care have a longer life span - saving your facility the cost of unnecessarily replacing your linens.

### Peace of Mind

A five-year limited warranty is issued on the frame, basket, shaft, beatings and seals if failure or breakage should occur during normal operation due to defects in material or workmanship that would prohibit its further use. In addition, a three-year limited warranty is issued to the original purchaser on all other parts.

### Specifications

Capacity - lb (kg)	18 (8.2)
Overall Width - in (mm)	26" (660)
Overall Depth - in (mm)	31 5/16" (796)
Overall Height - in (mm)	39 3/16" (995)
Cylinder Diameter - in (mm)	20 7/8" (530)
Cylinder Depth - in (mm)	13" (330)
Cylinder Volume - cu. ft. (liters)	2.68 (76)
Door Opening Size - in (mm)	11 13/16" (300)
Door Bottom To Floor - in (mm)	11" (279)
Wash Speed - RPM	10-50
Distribution Speed - RPM	85
Extract Speed - RPM	500-1000
Extract G-Force	296
Water Inlet Connection - in (mm)	3 x 3/4" (19)
Steam Inlet Connection - in (mm)	3/8" (10)
Drain Conn. Size - in (mm)	2" (50)
Motor Size - HP (kW)	1 (.75)
Voltage/Hz/Phase Circuit Breaker - FLA	
X	200-240/50-60 1/3 - 15
Q	N/A
P	380-415/50-60/3 - 15
N	440-480/50-60/3 - 15
Shipping Dimensions - in (mm)	
Height	46 1/16" (1170)
Width	28 3/4" (730)
Depth	33 1/16" (840)
Net Weight - lb (kg)	481 (218)
Shipping Weight - lb (kg)	514 (233)



### Control Option

#### P

39 cycles with the most flexible operation available in its class. This control must be used for spray rinse, super high G-force, or water re-use applications.